



Steam Cylinder Oil

TM

SAPON-A-MAX320320 COMPOUNDED CYLINDER OIL (ISO320)

9% Compounded 100% Loss Lubricant

For Saturated and Wet Steam under 160 psi and less than 370° F*

Green Velvet Steam Cylinder Oil® is formulated specifically for steam engine lubrication by reciprocating steam power engineers. It is custom blended to exacting standards so it will perform consistently day after day in most kinds of engine service.

SAPON-A-MAX320 Compounded Cylinder Oil is intended for low pressure and wet steam conditions that create severe water washing effects. These effects prevent a straight mineral oil or less compounded oil from forming an efficient film on rubbing surfaces inside the cylinders and valve chests. When properly atomized and dispersed in the steam at the engine inlet SAPON-A-MAX320 forms a tacky emulsion that is laden with high viscosity mineral oil. This oil laden emulsion adheres to the rubbing surfaces, resists the water washing effects and helps form an efficient lubricating film, thus reducing friction and galling in the cylinders and valve chests.

The high percentage of compounding in SAPON-A-MAX320 allows a conservative feed rate with good lubrication performance. However, the stable emulsions created in the cylinders are not susceptible to good separation from exhaust condensate that will be returned to the boiler as feed water. Where condensate purity in exhaust traps, condensers and hotwells is critical a lighter compounding or straight mineral cylinder oil fed at higher feed rates may be required.

SAPON-A-MAX320 GREEN VELVET STEAM CYLINDER OIL (ISO320)

Typical Specifications

Base Oil:	Paraffinic Base Stock
Compounding:	9% Refined Animal Fat
Additives:	Film/surface modifiers for 100% loss lubrication
Color:	Opaque Medium Green
Viscosity:	ISO320
Flash Point:	560° F C.O.C.
Carbon Residue:	0.85% Conradson

The chemical, physical and physiological properties of this product have not been fully investigated and it's handling, mixing with incompatible chemicals, or use may be hazardous. The product is for industrial use only. Do not ingest. Keep away from children. Material safety data sheets are available upon request.

No warranties, expressed or implied including patent warranties, or warranties of merchantability of fitness of use, are made by Lubrication Specialties Corporation with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

Revised 4/14/2010 ©January, 2002 by Lubrication Specialties Corporation Green Velvet Steam Cylinder Oil® is manufactured for and marketed by:

Lubrication Specialties Corporation
P.O. Box 1118
Fall City, Washington 98024 USA
Tel. 423-215-0684 <http://www.steamengine.lube.com>