



Steam Cylinder OilTM

SAPON-A-NON1000 NON-COMPOUNDED CYLINDER OIL

ISO1000 Non-compounded 100% Loss Lubricant

For Dry, Saturated Steam and Superheated Steam over 160 psi and less than 650° F*

Green Velvet Steam Cylinder Oil® is formulated specifically for steam engine lubrication by reciprocating steam power engineers. It is custom blended to exacting standards so it will perform consistently day after day in most kinds of engine service.

SAPON-A-NON1000 Non-compounded Cylinder Oil is intended for condensing and non-condensing, high temperature steam engines. It will establish efficient films in the valve chests and cylinders where high pressure, moderately superheated steam conditions ensure dry, difficult to lubricate conditions. When properly atomized and dispersed in the steam at the engine inlet SAPON-A-NON1000 resists thermal breakdown, spreads and wets the running surfaces quickly and helps form an efficient lubricating film, thus reducing friction and galling in the valve chests and cylinders. SAPON-A-NON1000 utilizes a high viscosity base oil blend that builds a tough lubricating film and withstands higher steam pressures over 160 psi.

SAPON-A-NON1000 should not be used at pressures below 160 psi and typically should be used at 200 psi or higher in large cylinders (bores of 8" or more). The elimination of compounding in SAPON-A-NON1000 allows a conservative feed rate with good lubrication performance and ensures complete separation from the exhaust condensate in condensing plants

SAPON-A-NON1000 NON-COMPOUNDED CYLINDER OIL – (ISO1000)

Typical Specifications

Base Oil:	Paraffinic Base Stock/Thickener Blend
Compounding:	None
Additives:	Film/surface modifiers for 100% loss lubrication
Color:	Opaque Dark Green
Viscosity:	ISO1000 (SAE250)
Flash Point:	600° F C.O.C.
Carbon Residue:	1.90% Conradson

The chemical, physical and physiological properties of this product have not been fully investigated and its handling, mixing with incompatible chemicals, or use may be hazardous. The product is for industrial use only. Do not ingest. Keep away from children. Material safety data sheets are available upon request.

No warranties, expressed or implied including patent warranties, or warranties of merchantability of fitness of use, are made by Lubrication Specialties Corporation with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.

Revised 4/15/10 ©May, 2004 by Lubrication Specialties Corporation Green Velvet Steam Cylinder Oil® is manufactured for and marketed by:

Lubrication Specialties Corporation
P.O. Box 1118
Fall City, Washington 98024
Tel. 423-215-0684 www.steamenginelube.com